Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Audio Wire and Cable

Electrolytic Tough Pitch (ETP) High-Conductivity Copper Speaker Cables
Parallel Zip Constructions

Jameco Part Number 232611
(9717-368-1000)

BRILLIANCE®

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
				Ft.	m	Lbs.	kg	Inch	mm	Inch	mm
24 AWG Stranded (7x32) ETP High-conductivity Copper • Parallel: (1) Tinned, (1) Bare											
PVC Insulation • PVC Jacket (Available in Clear, White, Brown or Chrome)											
300V 60°C (Clear) 300V 75°C (Chrome, Brown, White)	**8782**		2	U-1000 ▲ 1000 ◆	U-304.8 304.8	6.0 7.0	2.7 3.2	.017	.43	.058 x .116	1.47 x 2.95
22 AWG Stranded (7x30) ETP High-conductivity Copper • Parallel: (1) Tinned, (1) Bare											
PVC Insulation • Clear PVC Jacket											
300V 60°C	**9712**		2	1000	304.8	9.0	4.1	.017	.43	.065 x .130	1.65 x 3.30
20 AWG Stranded (7x28) ETP High-conductivity Copper • Parallel: (1) Tinned, (1) Bare											
PVC Insulation • Clear or Chrome PVC Jacket											
300V 60°C VW-1	**8649**		2	1000	304.8	12.0	5.5	.018	.46	.073 x .146	1.85 x 3.71
18 AWG Stranded (16x30) ETP High-conductivity Copper • Parallel: (1) Tinned, (1) Bare											
PVC Insulation • Clear PVC Jacket											
300V 60°C	**9708**		2	100 U-500 500 U-1000 1000	30.4 U-152.4 152.4 U-304.8 304.8	2.8 10.5 10.5 20.0 21.0	1.3 4.8 4.8 9.1 9.5	.032	.81	.110 x .220	2.79 x 5.59
16 AWG Stranded (26x30) ETP High-conductivity Copper • Parallel: (1) Tinned, (1) Bare											
PVC Insulation • Clear PVC Jacket											
300V 60°C	**9716**		2	U-1000 1000	U-304.8 304.8	8.0 7.0	3.6 3.2	.027	.69	.115 x .230	2.92 x 5.84
14 AWG Stranded (19x27) ETP High-conductivity Copper • Parallel: (1) Tinned, (1) Bare											
PVC Insulation • Clear PVC Jacket											
60°C	**9717**		2	U-1000 1000	U-304.8 304.8	43.0 42.0	19.5 19.1	.035	.89	.146 x .292	3.71 x 7.42
12 AWG Stranded (65x30) ETP High-conductivity Copper • Parallel: (1) Tinned, (1) Bare											
PVC Insulation • Clear PVC Jacket											
60°C	**9718**		2	500 1000	152.4 304.8	33.0 66.0	15.0 30.0	.045	1.14	.185 x .370	4.70 x 9.40

▲U-1000 ft. put-up available in Brown or Chrome only.
◆1000 ft. put-up available in White or Clear only.